

# 36V 8A LiFePO4 Battery Charger for 31.5V 10S LFP Cells Pack Technical Datasheet

---

Phonix Charger – Custom Smart Battery Charger Manufacturer

LiFePO4 Battery Charger: <https://phonixcharger.com/lifepo4-battery-charger/>

## Product Overview

This technical datasheet describes a 36V 8A 288W LiFePO4 Battery Charger designed for charging 10S 31.5V LiFePO4 battery packs. The charger provides stable constant current and constant voltage charging optimized for LiFePO4 battery chemistry.

The 36V 8A LiFePO4 battery charger is designed for charging 31.5V lithium iron phosphate (LFP) battery packs used in a wide range of applications, including electric scooters, e-bikes, power tools, portable power stations, solar energy storage systems, alarm and security systems, UPS backup power, industrial equipment, robotics, marine electronics, and other devices powered by 8-cells (10S) LiFePO4 batteries. The charger follows a safe multi-stage charging profile including pre-charge, constant current (CC), constant voltage (CV), and automatic charge termination.

Phonix provides OEM and ODM solutions for custom battery charging systems. As a [Custom](#) Battery Charger manufacturer, Phonix also offers custom smart charger design services for [lithium](#), [LiFePO4](#), [lead-acid](#), and [NiMH](#) battery applications.

## Key Features

- Multi-stage charging: Pre-charge, CC, CV and automatic cut-off
- Designed for 10S 31.5V LiFePO4 battery packs
- Wide AC input range 100 ~ 240V AC
- LED charging status indicator
- Multiple protections: OVP, OCP, short circuit and reverse protection
- High efficiency design  $\geq 91\%$
- Industrial compact design
- OEM / ODM customization available

## Technical Specifications

Parameter	Specification
Brand	Phonix
Model	FX36008000
AC Input	100~240V, 50/60Hz
Input Voltage Range	AC 90~264V
Rated Input Current	3.23A at 100Vac input
Max Input Power	323W
DC Output Voltage MAX	DC 36V
Output Voltage Range	DC 31.5V ~ 36V,
Charging Voltage	36V DC $\pm$ 10% , CV Mode.
Charging Current	8A $\pm$ 5%
Pre-charge Current	0.8A
Charge End Current	$\leq$ 0.8A $\pm$ 10%
Output Max Power	288W
Battery Type	10S 31.5V LiFePO4 Battery (10S 31.5V LFP Cells Pack)
Efficiency	$\geq$ 91%
Ripple Voltage	$\leq$ 360 mV
Operating Temperature	-10°C ~ +40°C
Storage Temperature	-40°C ~ +70°C
Humidity	0 ~ 95% RH
Cooling	Natural cooling
Size	233*108*64mm
Weight	1900g

Parameter	Specification
Safety Certifications	CE / UL / TUV / FCC / PSE / CCC / SAA / RCM / WEEE
MTBF	50000 Hours
Warranty	5 years

## Typical Applications

- 10S 31.5V LiFePO4 battery packs
- Electric scooters, e-bikes and light EV batteries
- Portable power stations and mobile power systems
- Solar energy storage and off-grid applications
- Backup power systems and UPS
- Security, alarm and surveillance systems
- Emergency lighting systems
- Industrial automation and robotics equipment
- Marine electronics and RV battery systems
- Portable medical and testing devices
- OEM / ODM custom LiFePO4 battery charging solutions

## Manufacturer Information

Manufacturer: Phonix

Whatsapp: +86-19124269133

Email: sales@phonixcharger.com

### Product Page:

<https://phonixcharger.com/36v-8a-lifepo4-battery-charger-for-10s-32v-lfp-packs/>

**Official Website:** <https://phonixcharger.com>



图 1: Phonix 36V8A LiFePO4 Battery Charger